



**MAGNASOFT TLC-Sample(1LB-0,454KG)  
Siloxane Polyalkyleneoxide Copolymer**

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Manufactured By:** Momentive Performance Materials  
3500 South State Route 2  
FRIENDLY WV 26146

**Revised:** 04/30/2008  
**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300

**Chemical Family/Use:** Textile Softener  
**Formula:** Siloxane Polyalkyleneoxide Copolymer

**HMIS**

Flammability: 2                      Reactivity: 0                      Health: 1

**NFPA**

Flammability: 2                      Reactivity: 0                      Health: 1

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

Attention! This material is not considered hazardous by the OSHA Hazard Communication Standard 29 CFR 1910.1200

Form: Liquid                      Color: Amber                      Odor: Mild polyether

**POTENTIAL HEALTH EFFECTS**

**INGESTION**

No adverse effects are expected under normal conditions of use.

**SKIN**

May cause mild skin irritation.

**INHALATION**

No adverse effects are expected under normal conditions of use.

**EYES**

Liquid splashed into the eye may cause discomfort. May cause the following effects: - excess redness of the conjunctivae - swelling of the conjunctivae - iridal inflammation

**MEDICAL CONDITIONS AGGRAVATED**

Skin contact may aggravate: - an existing dermatitis

**SUBCHRONIC (TARGET ORGAN )**

None known.

**CHRONIC EFFECTS / CARCINOGENICITY**

For additional information, please see Section 11, Toxicological Information.



**MAGNASOFT TLC-Sample(1LB-0,454KG)**  
**Siloxane Polyalkyleneoxide Copolymer**

**ROUTES OF EXPOSURE**

Eyes

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<b><u>A. HAZARDOUS</u></b>		
Polyalkylene Oxide	27274-31-3	10 - 30 %
<b><u>B. NON-HAZARDOUS</u></b>		
Siloxane Polyalkyleneoxide Copolymer	68937-54-2	60 - 90 %

**4. FIRST AID MEASURES**

**INGESTION**

Do NOT induce vomiting. If victim is conscious, give 2-4 glasses of water. Never give anything by mouth to an unconscious person. Obtain medical attention.

**SKIN**

Wash off with soap and water. Get medical attention if symptoms occur.

**INHALATION**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

**EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**NOTE TO PHYSICIAN**

Treatment is symptomatic and supportive.

**5. FIRE-FIGHTING MEASURES**

<b>FLASH POINT:</b>	114 °C; 237 °F
<b>METHOD:</b>	Pensky-Martens closed cup ASTM D 93
<b>FLAMMABLE LIMITS IN AIR - LOWER (%):</b>	Not available

**MAGNASOFT TLC-Sample(1LB-0,454KG)  
Siloxane Polyalkyleneoxide Copolymer**

---

**FLAMMABLE LIMITS IN AIR - UPPER (%):** Not available

**SENSITIVITY TO MECHANICAL IMPACT:** No

**SENSITIVITY TO STATIC DISCHARGE**  
Sensitivity to static discharge is not expected.

**EXTINGUISHING MEDIA**  
All standard extinguishing agents are suitable.

**SPECIAL FIRE FIGHTING PROCEDURES**  
Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

## **6. ACCIDENTAL RELEASE MEASURES**

**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**  
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

**ENVIRONMENTAL PRECAUTIONS**  
Do not flush into surface water or sanitary sewer system.

## **7. HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**  
Avoid contact with skin and eyes. Keep away from children. Attention: Not for injection into humans. May generate formaldehyde at temperatures greater than 150 C (300 F). See Section 10 of MSDS for details.

**STORAGE**  
Keep container closed. Store in original container.

**FURTHER INFORMATION ON STORAGE CONDITIONS**  
No data available

## **8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**ENGINEERING CONTROLS**  
Eyewash stations; Showers; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

**MAGNASOFT TLC-Sample(1LB-0,454KG)**  
**Siloxane Polyalkyleneoxide Copolymer**

**RESPIRATORY PROTECTION**

May be needed if product is used in a confined or poorly ventilated area. If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

**PROTECTIVE GLOVES**

Impermeable or chemical resistant gloves.

**EYE AND FACE PROTECTION**

Safety glasses

**OTHER PROTECTIVE EQUIPMENT**

Wear suitable protective clothing and eye/face protection.

**Exposure Guidelines**

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING POINT - C &amp; F:</b>	> 150 °C; > 302 °F; Copolymer
<b>VAPOR PRESSURE (20 C) (MM HG):</b>	< 1
<b>VAPOR DENSITY (AIR=1):</b>	> 1
<b>FREEZING POINT:</b>	-23 °C; -9 °F
<b>MELTING POINT:</b>	-23 °C; -9 °F
<b>PHYSICAL STATE:</b>	Liquid
<b>ODOR:</b>	Mild polyether
<b>COLOR:</b>	Amber
<b>EVAPORATION RATE (BUTYL ACETATE=1):</b>	< 1
<b>DENSITY:</b>	1.074 g/cm3
<b>VOLATILE ORGANIC CONTENT (VOL):</b>	Not determined
<b>SOLUBILITY IN WATER (20 C):</b>	Soluble
<b>VOC EXCL. H2O &amp; EXEMPTS (G/L):</b>	17.40



**MAGNASOFT TLC-Sample(1LB-0,454KG)**  
**Siloxane Polyalkyleneoxide Copolymer**

**10. STABILITY AND REACTIVITY**

**HAZARDOUS POLYMERIZATION**

Will not occur

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS**

Burning can produce the following combustion products:; Oxides of carbon.; Oxides of silicon.; Formaldehyde; Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant.; Acute overexposure to the products of combustion may result in irritation of the respiratory tract.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

None known.

**CONDITIONS TO AVOID**

None known.

**11. TOXICOLOGICAL INFORMATION**

**ACUTE ORAL**

LD50; Species: Rat.; > 5,000 mg/kg;

**ACUTE DERMAL**

LD50; Species: Rat.; > 2,000 mg/kg;

**ACUTE INHALATION**

Remarks: No data available

**SENSITIZATION**

Species: Guinea pig; Result: Negative. Method: Buehler Test.

**SKIN IRRITATION**

Species: Rabbit.; Result: Mild skin irritation

**EYE IRRITATION**

Species: Rabbit. ; Result: Mild eye irritation

**MUTAGENICITY**

Negative in the Ames test.

**OTHER EFFECTS OF OVEREXPOSURE**

No adverse effects anticipated from available information.



**MAGNASOFT TLC-Sample(1LB-0,454KG)  
Siloxane Polyalkyleneoxide Copolymer**

**12. ECOLOGICAL INFORMATION**

**ECOTOXICOLOGY**

All available ecological data have been taken into account for the development of the hazard and precautionary information contained in this Safety Data Sheet.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORT INFORMATION**

**DOT SHIPPING NAME:** Combustible liquid, n.o.s.  
**DOT HAZARD CLASS:** CBL  
**DOT LABEL (S):** NON  
**UN/NA NUMBER:** NA 1993  
**PACKING GROUP:** III

**Further Information:** This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

**15. REGULATORY INFORMATION**

**Inventories**

Korea Existing Chemicals Inventory (KECI)	y (Positive listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (Positive listing)
EU list of existing chemical substances	y (Positive listing)
Australia Inventory of Chemical Substances (AICS)	y (Positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (Positive listing)
TSCA list	y (Positive listing)
China Inventory of Existing Chemical Substances	y (Positive listing)



**MAGNASOFT TLC-Sample(1LB-0,454KG)**  
**Siloxane Polyalkyleneoxide Copolymer**

---

Canada DSL Inventory y (Positive listing)  
For inventories that are marked as quantity restricted or special cases, please contact Momentive.

**US Regulatory Information**

**SARA (311,312) HAZARD CLASS**  
Fire Hazard

**SARA (313) CHEMICALS**

**CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

**Canadian Regulatory Information**

**WHMIS HAZARD CLASS**  
D2A VERY TOXIC MATERIALS

**16. OTHER INFORMATION**

**OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found  
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).