



SAG® 1000 foam control agent
Polydimethylsiloxane

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Momentive Performance Materials
3500 South State Route 2
FRIENDLY WV 26146

Revised: 02/19/2008
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Polydimethylsiloxane
Formula: Polydimethylsiloxane

HMIS

Flammability: 1 Reactivity: 0 Health: 0

NFPA

Flammability: 1 Reactivity: 0 Health: 0

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Normal precautions common to safe manufacturing practice should be followed in handling and storage.
Form: Liquid Color: Translucent Odor: Mild

POTENTIAL HEALTH EFFECTS

INGESTION

No evidence of harmful effects from available information.

SKIN

No evidence of harmful effects from available information.

INHALATION

Short-term harmful health effects are not expected from vapor generated at ambient temperature.

EYES

May cause slight irritation. May cause the following effects: - swelling of the conjunctivae

MEDICAL CONDITIONS AGGRAVATED

A knowledge of the available toxicology information and of the physical and chemical properties of the material suggests that overexposure is unlikely to aggravate existing medical conditions.

SUBCHRONIC (TARGET ORGAN)

None known.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen



SAG® 1000 foam control agent
Polydimethylsiloxane

or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

No anticipated routes of exposure.

3. COMPOSITION / INFORMATION ON INGREDIENTS

PRODUCT COMPOSITION

CAS REG NO.

WGT. %

A. HAZARDOUS

B. NON-HAZARDOUS

Polydimethylsiloxane	63148-62-9	> 90 %
Silica Filled Polydimethylsiloxane	Trade secret	10 - 30 %

4. FIRST AID MEASURES

INGESTION

No emergency care anticipated.

SKIN

Wash skin with soap and water.

INHALATION

No emergency care anticipated.

EYES

Flush eyes thoroughly with water for several minutes.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

268 °C; 514 °F

METHOD:

Pensky-Martens closed cup ASTM D 93

FLAMMABLE LIMITS IN AIR - LOWER (%):

Not available

FLAMMABLE LIMITS IN AIR - UPPER (%):

Not available

SENSITIVITY TO MECHANICAL IMPACT:

No



SAG® 1000 foam control agent
Polydimethylsiloxane

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

PRECAUTIONS FOR FIRE-FIGHTING

Do not direct a solid stream of water or foam into hot, burning pools: this may cause frothing and increase fire intensity.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

ENVIRONMENTAL PRECAUTIONS

Do not flush into surface water or sanitary sewer system.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Keep away from children. Attention: Not for injection into humans. May generate formaldehyde at temperatures greater than 150 C (300 F). See Section 10 of MSDS for details.

STORAGE

Keep container closed. Store in original container.

FURTHER INFORMATION ON STORAGE CONDITIONS

No data available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers; Ventilation and other forms of engineering controls are preferred for

SAG® 1000 foam control agent
Polydimethylsiloxane

controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

RESPIRATORY PROTECTION

May be needed if product is used in a confined or poorly ventilated area. If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Impermeable or chemical resistant gloves.

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	> 150 °C; > 302 °F
VAPOR PRESSURE (20 C) (MM HG):	< 1
VAPOR DENSITY (AIR=1):	Heavier than air
FREEZING POINT:	< -50 °C; < -58 °F
MELTING POINT:	< -50 °C; < -58 °F
PHYSICAL STATE:	Liquid
ODOR:	Mild
COLOR:	Translucent
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
DENSITY:	1.0220 g/cm ³
VOLATILE ORGANIC CONTENT (VOL):	Not determined
SOLUBILITY IN WATER (20 C):	Insoluble
VOC EXCL. H₂O & EXEMPTS (G/L):	0



SAG® 1000 foam control agent
Polydimethylsiloxane

10. STABILITY AND REACTIVITY

STABILITY

Stable.

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Burning can produce the following combustion products: Oxides of carbon.; Oxides of silicon.; Formaldehyde.; Carbon monoxide is highly toxic if inhaled; carbon dioxide in sufficient concentrations can act as an asphyxiant.; Acute overexposure to the products of combustion may result in irritation of the respiratory tract.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None currently known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

OTHER EFFECTS OF OVEREXPOSURE

No adverse effects anticipated from available information.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGY

All available ecological data have been taken into account for the development of the hazard and precautionary information contained in this Safety Data Sheet.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION



SAG® 1000 foam control agent
Polydimethylsiloxane

Further Information: This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Korea Existing Chemicals Inventory (KECI)	y (Positive listing)
EU list of existing chemical substances	y (Positive listing)
Australia Inventory of Chemical Substances (AICS)	y (Positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (Positive listing)
TSCA list	y (Positive listing)
China Inventory of Existing Chemical Substances	y (Positive listing)
Canada DSL Inventory	y (Positive listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS
No SARA Hazards

SARA (313) CHEMICALS

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

Canadian Regulatory Information

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty,



SAG® 1000 foam control agent
Polydimethylsiloxane

either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).