

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer****1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

**Manufactured By:** Waterford Plant  
260 Hudson River Rd  
Waterford NY 12188

**Revised:** 01/20/2010  
**Preparer:** PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS  
**CHEMTREC** 1-800-424-9300

**Chemical Family/Use:** Silicone Fluid  
**Formula:** Polyetherpolysiloxane

**HMIS**

Flammability: 1      Reactivity: 0      Health: 0

**NFPA**

Flammability: 1      Reactivity: 0      Health: 0

**2. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

Attention! This material is not considered hazardous by the OSHA Hazard Communication Standard 29 CFR 1910.1200

**Form:** liquid**Color:** colourless to yellowish**Odor:** mild**POTENTIAL HEALTH EFFECTS****INGESTION**

No adverse effects are expected under normal conditions of use.

**SKIN**

May cause mild skin irritation.

**INHALATION**

No adverse effects are expected under normal conditions of use.

**EYES**

May cause eye irritation.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**CHRONIC EFFECTS / CARCINOGENICITY**

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer****ROUTES OF EXPOSURE**

No anticipated routes of exposure.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<b><u>A. HAZARDOUS</u></b>		
2-Propanol	67-63-0	1 - 5 %
<b><u>B. NON-HAZARDOUS</u></b>		
Siloxane Polyalkyleneoxide Copolymer	68937-55-3	60 - 100 %
mono-2-propenyl ether methyloxirane	9041-33-2	10 - 30 %

**4. FIRST AID MEASURES****INGESTION**

Do NOT induce vomiting. If victim is conscious, give 2 glasses of water. Never give anything by mouth to an unconscious person. Obtain medical attention.

**SKIN**

Wash off with soap and water. Get medical attention if symptoms occur.

**INHALATION**

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

**EYES**

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**NOTE TO PHYSICIAN**

Treatment is symptomatic and supportive.

**5. FIRE-FIGHTING MEASURES****FLASH POINT:** > 100 °C; 212 °F

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer**

---

**IGNITION TEMPERATURE:** Unknown  
**FLAMMABLE LIMITS IN AIR - LOWER (%):** not applicable  
**FLAMMABLE LIMITS IN AIR - UPPER (%):** not applicable

**SENSITIVITY TO MECHANICAL IMPACT:** No

**SENSITIVITY TO STATIC DISCHARGE**  
Sensitivity to static discharge is not expected.

**EXTINGUISHING MEDIA**  
All standard extinguishing agents are suitable.

**SPECIAL FIRE FIGHTING PROCEDURES**  
Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

**6. ACCIDENTAL RELEASE MEASURES**

**ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED**  
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section.

**7. HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE**  
Avoid contact with skin and eyes. Keep away from children. Attention: Not for injection into humans. May generate formaldehyde at temperatures greater than 150 C (300 F). See Section 10 of MSDS for details.

**STORAGE**  
Store at room temperature in the original container. Keep container closed.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**ENGINEERING CONTROLS**  
Eyewash stations; Use only in well-ventilated areas.

**RESPIRATORY PROTECTION**  
If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer**

(see 29CFR 1910.134).

**PROTECTIVE GLOVES**

Impermeable or chemical resistant gloves.

**EYE AND FACE PROTECTION**

Safety glasses with side-shields

**OTHER PROTECTIVE EQUIPMENT**

Wear suitable protective clothing and eye/face protection.

**Exposure Guidelines**

<b>Component</b>	<b>CAS RN</b>	<b>Source</b>	<b>Value</b>
2-Propanol	67-63-0	OSHA Z1PEL	400 ppm; 980 mg/m <sup>3</sup>
2-Propanol	67-63-0	ACGIH, TWA	200 ppm
2-Propanol	67-63-0	ACGIH, STEL	400 ppm
2-Propanol	67-63-0	ACGIH,	Listed.
2-Propanol	67-63-0	OSHA Z1,	Listed.

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>BOILING POINT - C &amp; F:</b>	no data available
<b>VAPOR PRESSURE (20 C) (MM HG):</b>	negligible
<b>VAPOR DENSITY (AIR=1):</b>	no data available
<b>FREEZING POINT:</b>	no data available
<b>PHYSICAL STATE:</b>	liquid
<b>ODOR:</b>	mild
<b>COLOR:</b>	colourless to yellowish
<b>SPECIFIC GRAVITY (WATER=1):</b>	ca. 1.04
<b>DENSITY:</b>	ca. 1.059 g/cm <sup>3</sup>
<b>ACID / ALKALINITY (MEQ/G):</b>	~7
<b>pH:</b>	not applicable
<b>SOLUBILITY IN WATER (20 C):</b>	partly soluble
<b>SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):</b>	Soluble in toluene
<b>VOLATILE ORGANIC CONTENT:</b>	< 1.0 %(m)

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer**

---

**10. STABILITY AND REACTIVITY****STABILITY**

Stable

**HAZARDOUS POLYMERIZATION**

Will not occur.

**HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS**

Carbon dioxide (CO<sub>2</sub>); Carbon monoxide; Silicon dioxide.; formaldehyde-like; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

**INCOMPATIBILITY (MATERIALS TO AVOID)**

Avoid contact with acids, bases, or oxidizing agents.

**CONDITIONS TO AVOID**

None known.

**11. TOXICOLOGICAL INFORMATION****ACUTE ORAL**

LD50; Species: rat; &gt; 5,000 mg/kg;

**ACUTE DERMAL**

LD50; Species: rabbit; &gt; 2,000 mg/kg;

**ACUTE INHALATION**

Remarks: None known.

**OTHER**

Product tested as non-irritating to the eyes (rabbit), mildly irritating to the skin (rabbit). Product also tested as having weak and insignificant allergenic potential (guinea pig) according to the Kligman Maximization Test. It actually scored 0% sensitization according to the test protocol. Isopropyl alcohol has produced developmental effects and reduced fetal weight in animals following inhalation exposure.

**SENSITIZATION**

no data available

**SKIN IRRITATION**

Species: rabbit; Result: Mild skin irritation. Method: Draize Test.

**EYE IRRITATION**

Species: rabbit ; Result: No eye irritation. Method: Draize Test.

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer**

---

**MUTAGENICITY**

Negative in the Ames test.

**12. ECOLOGICAL INFORMATION****ECOTOXICITY**

no data available

**DISTRIBUTION**

no data available

**CHEMICAL FATE**

no data available

**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHOD**

Disposal should be made in accordance with federal, state and local regulations.

**14. TRANSPORT INFORMATION****Further Information:**

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

**15. REGULATORY INFORMATION****Inventories**

Canada DSL Inventory	y (positive listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer**

---

Philippines Inventory of Chemicals and Chemical Substances (PICCS) y (positive listing)  
TSCA list y (positive listing) On TSCA Inventory  
EU list of existing chemical substances y (positive listing)  
Canada NDSL Inventory n (Negative listing)  
For inventories that are marked as quantity restricted or special cases, please contact Momentive.

**US Regulatory Information****CERCLA**

Reportable quantity: 10000 lbs

**PRODUCT COMPOSITION**

Isopropyl Alcohol

**Chemical**

67-63-0

**CERCLA Reportable Quantity**

Reportable quantity: 100 LBS

**SARA (311,312) HAZARD CLASS**

Acute Health Hazard; Chronic Health Hazard

**SARA (313) CHEMICALS**

67-63-0, Isopropyl Alcohol.

**CALIFORNIA PROPOSITION 65**

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

**Canadian Regulatory Information****WHMIS HAZARD CLASS**

D2A - Very Toxic Material Causing Other Toxic Effects

**Other****SCHDLE B/HTSUS:** 3910.00.0000 Silicones in primary forms**ECCN:** EAR99**16. OTHER INFORMATION****OTHER**

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are

**SF1188A 55G-Drum (450.0LBS-204.30KG)  
Silicone polyether copolymer**

---

appropriate., C = ceiling limit      NEGL = negligible EST = estimated      NF = none found  
NA = not applicable      UNKN = unknown NE = none established      REC = recommended ND =  
none determined      V = recommended by vendor SKN = skin      TS = trade secret R =  
recommended      MST = mist NT = not tested      STEL = short term exposure limit ppm =  
parts per million      ppb = parts per billion By-product= reaction by-product, TSCA inventory status  
not required under 40 CFR part 720.30(h-2).