Elementis Specialties, Inc.	Elementis GmbH
P.O. Box 700, Wyckoffs Mill Rd.	Technical Centre
Hightstown, NJ 08520	Stolberger Strasse 370
Tel.: +1-609-443 2500	50933 Cologne, Germany
Fax: +1-609-443 2422	Tel: +49 (0)221 2923 2000
specialinfo.usa@elementis-na.com	Fax: +49 (0)221 2923 2010
Web: www.elementis-specialties.com	specialinfo.eu@elementis-eu.com



LIPGLOSS KR9/135

Lipgloss containing FANCOR® ABYSSINIAN OIL, MEADOWESTOLIDE® and BENTONE GEL® ABO V.

Advantages

The presence of FANCOR $^{\!0}$ ABYSSINIAN OIL, MEADOWESTOLIDE $^{\!0}$ and BENTONE GEL $^{\!0}$ ABO V in this system:

- Aide smooth application
- Stabilize the pigments
- Soften the lips

Ingredient	Supplier	% w/w	
PHASE A			
BENTONE GEL [®] ABO V (Crambe Abyssinica Seed Oil, Disteardimonium Hectorite and Propylene Carbonate)	ELEMENTIS Specialties	3.5	
MEADOWESTOLIDE® (Meadowfoam Estolide)	ELEMENTIS Specialties	3.0	
Penreco Snow (Petrolatum)	Penreco	12.9	
Cloisonne Red 424C (Mica, Titanium Dioxide and Carmine)	BASF	7.5	
Flamenco Ultrasilk 2500 (Mica and Titanium Dioxide)	BASF	5.0	
Syncrowax HGIC (C ₁₈₋₃₆ Acid Triglyceride)	Croda	2.0	
Yellow Iron Oxide		0.3	
Germaben Plus (Diazolidinyl Urea, Iodopropynyl Butylcarbamate)	ISP	0.3	
Propylparaben		0.15	
PHASE B			
FANCOR® ABYSSINIAN OIL (Crambe Abyssinica Seed Oil)	ELEMENTIS Specialties	64.15	
D&C Red 6 Aluminium Lake		1.2	

Method of Manufacture

- 1. Heat Phase A to 85°C and mix.
- 2. Add premixed Phase B and mix.
- 3. Cool to 55°C and fill.

N.B.

Please refer to the Product Data Sheets for additional advice on incorporation.

The information herein is currently believed to be accurate. We do not guarantee its accuracy. Purchasers shall not rely on statements herein when purchasing any products. Purchasers should make their own investigations to determine if such products are suitable for a particular use. The products discussed are sold without warranty, express or implied, including a warranty of merchantability and fitness for use. Purchases will be subject to a separate agreement which will not incorporate this document.