

# Carbopol<sup>®</sup>\* 674 Polymer

**General:** White powder  
Slight acetic odor

PRODUCT SPECIFICATION	MINIMUM	MAXIMUM	TEST FREQUENCY	LUBRIZOL PROCEDURE NUMBER
<b>Viscosity, 0.2 wt% Mucilage**, Brookfield RVT, (mPa·s)</b> (20 rpm @ 25°C)	3,500	8,500	Once / 20 Lots	430-I
<b>Viscosity, 0.5 wt% Mucilage**, Brookfield, RVT, (mPa·s)</b> (20 rpm @ 25°C)	5,000	13,000	Once / Lot	430-I
<b>Moisture Content (Loss on Drying)</b> (wt%)	--	3.0	Once / 10 Lots	SA-004

\*\*A mucilage is defined as a polymer dispersion in water neutralized to pH 7.5 with NaOH.

NOTE: Lubrizol Standard Test Procedures should be followed to insure reproducibility with Certificate of Analysis results. Test Procedures available at [www.homecare.noveon.com](http://www.homecare.noveon.com) or upon request.

Original Date of Issue: May, 1995  
Previous Editions: November, 2001 / February, 2009

**Lubrizol Advanced Materials, Inc. / 9911 Brecksville Road, Cleveland, Ohio 44141-3247 / TEL: 800.379.5389 or 216.447.5000**

Lubrizol Advanced Materials, Inc. cannot guarantee how the product(s) will perform in combination with other substances or in the user's process. Therefore, no representations, guarantees or warranties of any kind are made as to the suitability of this product(s) for particular applications. End product performance is

the responsibility of the user. Lubrizol Advanced Materials, Inc. shall not be liable for and the customer assumes all risk and liability of any use or handling of any material beyond Lubrizol Advanced Materials' direct control. The SELLER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING,

BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE. Nothing contained herein is to be considered as permission, recommendation, nor as an inducement to practice any patented invention without permission of the patent owner.

For further information, please visit [www.homecare.noveon.com](http://www.homecare.noveon.com)